

Amendments to the Claims:

Please amend Claims 1, 3-6, 8, 10, 11, 16, 17 and 19 as follows:

Sub
DL
1 (currently amended): A liquid crystal display comprising:

a pair of substrates which face each other and a liquid crystal held therebetween;

a plurality of source lines and a plurality of gate lines arranged in a matrix on one of the pair of substrates, the plurality of source lines being divided at least into ~~two groups~~ a first and second group in a direction of extension of the source lines, such that at least one of the source lines does not extend across at least one of the gate lines;

a first source driver to apply image signals to ~~one~~ the first group of the divided source lines;

a second source driver to apply image signals to ~~the other~~ the second group of the divided source lines;

a first gate driver to apply scanning signals to the plurality of gate lines that extend across the ~~one~~ first group of the divided source lines;

a second gate driver to apply scanning signals to the plurality of gate lines that extend across the ~~other~~ second group of the divided source lines;
and

a switching unit to switch and allocate an image signal from each of the first and second source drivers to a predetermined number of the source lines from the first and second group of the divided source lines where the predetermined number of the source lines is less than a number of source lines in either of the first and second groups.

2. (original): A liquid crystal display according to Claim 1, wherein the predetermined number of source lines is two to four.

3. (currently amended): A liquid crystal display according to ~~Claim 2~~ claim 1, wherein the predetermined number of source lines is three.

4. (currently amended): A liquid crystal display according to ~~Claim 3~~ claim 1, wherein image signals having inverse polarities are output from adjacent outputs of the first and second source drivers.

5. (currently amended): A liquid crystal display according to ~~claim 3~~ claim 1, wherein image signals having inverse polarities are output from opposing outputs of the first and second source drivers.

6. (currently amended): A liquid crystal display according to ~~claim 3~~ claim 1, wherein scanning signals are applied substantially symmetrically by each gate driver.

7. (previously presented): A liquid crystal display according to claim 6, wherein the first gate driver applies scanning signals starting from a gate line most proximate to the first source driver and proceeding towards a gate line most distal to the first gate driver.

8. (currently amended): A liquid crystal display according to ~~claim 7~~ claim 6, wherein the second gate driver applies scanning signals starting from a gate line most proximate to the second source driver and proceeding towards a gate line most distal to the second gate driver.

9. (previously presented): A liquid crystal display according to claim 6, wherein each scanning signal applied by the first gate driver is substantially simultaneous with the symmetric scanning signal applied by the second gate driver.

10. (currently amended): A method of ~~increasing ease of~~ writing in a liquid crystal display, the method comprising:

selecting two sets of image signals, each image signal selected from a plurality of image signals;

applying each set of image signals at least to one of two groups a first and second group of divided source lines; and

applying scanning signals to two groups a first and second groups of gate lines, each group of gate lines correspondingly extending across a corresponding group the first and second groups of the divided source lines such that at least one of the source lines does not extend across at least one of the gate lines[[]];

switching the image signal from each of a first and a second source drivers to a predetermined number of source lines from the first and second groups of divided source lines where the predetermined number is less than a number of source lines in either of the first and second groups; and allocating the image signal from each of the first and the second source drivers to the predetermined number of source lines.

11. (currently amended): The method of claim 10, wherein the selecting comprising switching and allocating comprises demultiplexing each of the image signal from the plurality of image signals each of the first and second source drivers to the predetermined number of source lines.

12. (previously presented): The method of claim 10, further comprising dividing the source lines into two groups of source lines and the gate lines into two groups of gate lines.

13. (previously presented): The method of claim 10, further comprising inverting polarities of adjacent image signals of each of the two groups of image signals.

14. (previously presented): The method of claim 10, further comprising applying one scanning signal to one of the two groups of gate lines substantially simultaneously with applying one scanning signal to the other of the two groups of gate lines.

15. (previously presented): The method of claim 14, further comprising applying the scanning signals substantially symmetrically between the two groups of gate lines.

16. (currently amended): The method of ~~claim 15~~ claim 14, further comprising applying the scanning signals to the two groups of gate lines such that the substantially simultaneously applied scanning signals progressively approach each other.

17. (currently amended): The method of ~~claim 15~~ claim 14, further comprising applying the scanning signals to the two groups of gate lines such that the substantially simultaneously applied scanning signals remain the same distance from each other.

18. (previously presented): The method of claim 10, further comprising balancing a writing time of the image signals on the selected source lines with a capacitance formed at areas of overlap of the source lines and gate lines to provide a desired increase in ease of writing.

19. (currently amended): A liquid crystal display comprising:

a pair of substrates which face each other and a liquid crystal held therebetween;

a plurality of source lines and a plurality of gate lines arranged in a matrix, the plurality of source lines being divided at least into two groups a first and second group in a direction of extension of the source lines, such that at least one of the source lines in each group does not extend across at least one of the gate lines;

a first source driver to apply image signals to ~~one~~ the first group of the divided source lines;

a second source driver to apply image signals to the ~~other~~ second group of the divided source lines;

a first gate driver to apply scanning signals to the plurality of gate lines that extend across the ~~one~~ first group of the divided source lines;

a second gate driver to apply scanning signals to the plurality of gate lines that extend across the ~~other~~ second group of the divided source lines;
and

a switching unit to switch and allocate an image signal from each of the first and second source drivers to a predetermined number of the source lines from the first and second groups of the divided source lines where the predetermined number of the source lines is less than a number of source lines in either the first and second groups.

20. (previously presented): A liquid crystal display according to claim 19, wherein scanning signals are applied substantially symmetrically by each gate driver.

21. (previously presented): A liquid crystal display according to claim 1, wherein the plurality of gate lines that extend across the one group of the divided source lines do not extend across the other group of the divided source lines.